
Abrasive cloth, waterproof

CS 416 Y





Properties

Bonding agent	Resin
Grain	Zirconia alumina
Coating	Semi-open
Backing	Y-polyester

Product benefit

Very high aggressiveness and abrasive performance - Long service life also when used on materials that cause clogging

Application

Stainless steel	●
Plastic	●
NF metals	◑

Applications

- Railing construction
- Wall and façade builder
- Apparatus and container manufacturing
- Foundries

Available grits:

16 | 24 | 30 | 36 | 40 | 50 | 60 | 80 | 100 | 120 | 150 | 180 | 220 | 240 | 280 | 320 | 360 | 400 | 500 | 600 | 800 | 1000 | 1200 | 1500 | 2000 | 2500 | 3000

Width x Length in mm	grain	type of joint	type of coat.abras.	Packing unit/pcs.	Cat. number
75 x 2000	36	F4G butt joint	CS 416 Y	10	204858
75 x 2000	40	F4G butt joint	CS 416 Y	10	205377
75 x 2000	60	F4G butt joint	CS 416 Y	10	207651
75 x 2000	80	F4G butt joint	CS 416 Y	10	220805
150 x 2000	36	F4G butt joint	CS 416 Y	10	231336
150 x 2000	40	F4G butt joint	CS 416 Y	10	205474

Klingspor Schleifsysteme GmbH und Co. KG
Hüttenstraße 36 - 35708 Haiger - Germany
Fon + 49 (0) 2773 922-0 Fax + 49 (0) 2773 922-186
sales@klingspor.de - www.klingspor.de

Width x Length in mm	grain	type of joint	type of coat.abras.	Packing unit/pcs.	Cat. number
150 x 2000	60	F4G butt joint	CS 416 Y	10	204213
150 x 2000	80	F4G butt joint	CS 416 Y	10	205130

Klingspor Schleifsysteme GmbH und Co. KG
Hüttenstraße 36 - 35708 Haiger - Germany
Fon + 49 (0) 2773 922-0 Fax + 49 (0) 2773 922-186
sales@klingspor.de - www.klingspor.de