Cutting-off wheel

A 24 R SUPRA

Properties

Bonding agent	Synthetic resin, fibre-reinforced
Type of grain	Aluminium oxide
Bond	■■■■■□□
Aggression	■■■■□□□
Service life	■■■■■■□

Product benefit

Optimized combination for use on steel - Can be used on stainless steel - Good cutting properties - Optimal for stationary 3 - 5 kW cutting-off machine

Application

Steel	●
Stainless steel	◑
Castings	◑

Applications

- Plant engineering
- Apparatus and container manufacturing
- Metal construction
- Locksmith's shop

Diameter x Width x Bore in mm	Form	Vmax m/s	Max. RPM	Packing unit/pcs.	Cat. number
250 x 3 x 32		100 m/s	7600 rpm	10	2465
300 x 3 x 22,23		100 m/s	6400 rpm	10	71365
300 x 3 x 25,4		100 m/s	6400 rpm	10	6793
300 x 3 x 30		100 m/s	6400 rpm	10	13524
300 x 3 x 32		100 m/s	6400 rpm	10	6807
350 x 3,5 x 25,4		100 m/s	5500 rpm	10	13528
350 x 3,5 x 32		100 m/s	5500 rpm	10	13536
400 x 4,5 x 25,4		100 m/s	4800 rpm	10	292933

Klingspor Schleifsysteme GmbH und Co. KG
Hüttenstraße 36 - 35708 Haiger - Germany
Fon + 49 (0) 2773 922-0 Fax + 49 (0) 2773 922-186
sales@klingspor.de - www.klingspor.de

Diameter x Width x Bore in mm	Form	Vmax m/s	Max. RPM	Packing unit/pcs.	Cat. number
400 x 4,5 x 32		100 m/s	4800 rpm	10	292932
400 x 4,5 x 40		100 m/s	4800 rpm	10	296567

Klingspor Schleifsysteme GmbH und Co. KG
Hüttenstraße 36 - 35708 Haiger - Germany
Fon + 49 (0) 2773 922-0 Fax + 49 (0) 2773 922-186
sales@klingspor.de - www.klingspor.de