Cutting-off wheel

A 646 R SUPRA



Fe·S·Cl <0,1%



Properties

Bonding agent	Synthetic resin, fibre-reinforced
Type of grain	Aluminium oxide
Bond	■■■■■■□
Aggression	■■■■■■□
Service life	■■■■■■□

Product benefit

Free of iron, sulphur and chlorine - Universal use on steel and stainless steel - Cutting disc made of self-sharpening, calcined aluminum oxide - Tremendous aggressiveness when used for cutting solid steel materials

Application

Steel	●
Stainless steel	◑

Applications

- Plant engineering
- Apparatus and container manufacturing
- Metal construction
- Locksmith's shop
- Stainless steel processing industry
- Railing construction

Diameter x Width x Bore in mm	Form	Vmax m/s	Max. RPM	Packing unit/pcs.	Cat. number
115 x 1,6 x 22,23	▬	80 m/s	13300 rpm	25	340947
125 x 1,6 x 22,23	▬	80 m/s	12200 rpm	25	340946
150 x 1,6 x 22,23	▬	80 m/s	10200 rpm	25	340945
180 x 1,6 x 22,23	▬	80 m/s	8500 rpm	25	340944
230 x 1,9 x 22,23	▬	80 m/s	6600 rpm	25	340943
230 x 1,9 x 22,23	⌒	80 m/s	6600 rpm	25	340942

Klingspor Schleifsysteme GmbH und Co. KG
Hüttenstraße 36 - 35708 Haiger - Germany
Fon + 49 (0) 2773 922-0 Fax + 49 (0) 2773 922-186
sales@klingspor.de - www.klingspor.de

KLINGSPOR