Small cutting-off wheel

A 660 R *SUPRA*





Properties

Bonding agent	Synthetic resin, fibre-reinforced
Type of grain	Aluminium oxide
Bond	■■■■■□□
Aggression	■■■■■■□
Service life	■■■■■□□

Product benefit

Minimal burr formation - For universal use in hard-to-reach areas - For cutting tins, profiles and solid materials

Application

Steel	●
Stainless steel	●

Applications

- Plant engineering
- Apparatus and container manufacturing
- Metal construction
- Locksmith's shop
- Stainless steel processing industry
- Railing construction

Diameter x Width x Bore in mm	Form	Vmax m/s	Max. RPM	Packing unit/pcs.	Cat. number
100 x 1 x 10	▬▬	80 m/s	15300 rpm	25	368876
50 x 1 x 6	▬▬	80 m/s	30600 rpm	40	368881
76 x 1 x 10	▬▬	80 m/s	20100 rpm	40	368879
76 x 1 x 6	▬▬	80 m/s	20100 rpm	40	368880
76 x 1,6 x 10	▬▬	80 m/s	20100 rpm	40	368877
76 x 1,6 x 6	▬▬	80 m/s	20100 rpm	40	368878

Klingspor Schleifsysteme GmbH und Co. KG
Hüttenstraße 36 - 35708 Haiger - Germany
Fon + 49 (0) 2773 922-0 Fax + 49 (0) 2773 922-186
sales@klingspor.de - www.klingspor.de