
Cutting-off wheel
EDGE *SPECIAL*



Fe·S·Cl <0,1%



Properties

Bonding agent	Synthetic resin, fibre-reinforced
Type of grain	Aluminium oxide
Bond	■■■■■■
Aggression	■■■■■■□
Service life	■■■■■■

Product benefit

High-performance cutting-off wheel with self-sharpening abrasive grain - Great cutting performance combined with a long service life - Wide range of applications - 10 pieces in a tin with viewing window for easy removal

Application

Stainless steel	●
Steel	●
Aluminium	●

Applications

- Plant engineering
- Apparatus and container manufacturing
- Metal construction
- Locksmith's shop
- Stainless steel processing industry
- Railing construction
- Oil and gas industry
- Pipeline construction

Diameter x Width x Bore in mm	Form	Vmax m/s	Max. RPM	Packing unit/pcs.	Cat. number
115 x 1,2 x 22,23	▬▬	80 m/s	13300 rpm	50	362578
125 x 1,2 x 22,23	▬▬	80 m/s	12200 rpm	50	362579

Klingspor Schleifsysteme GmbH und Co. KG
Hüttenstraße 36 - 35708 Haiger - Germany
Fon + 49 (0) 2773 922-0 Fax + 49 (0) 2773 922-186
sales@klingspor.de - www.klingspor.de